

Product Summary

$V_{(BR)DSS}$	$R_{DS(on)MAX}$	I_D
80V	3.3mΩ@10V	90A


Feature

- Split gate trench MOSFET technology
- Excellent package for heat dissipation
- High density cell design for low RDS(ON)
- Suffix "-Q1" for AEC-Q101

Application


- DC/DC Converter
- Power switching application
- Uninterruptible power supply

Package




PDFN5*6-8L

Circuit diagram



Marking



Absolute maximum ratings ($T_A=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	80	V
Gate-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current ($T_C=25^{\circ}\text{C}$)	I_D	90	A
Continuous Drain Current ($T_C=100^{\circ}\text{C}$)	$I_D (100^{\circ}\text{C})$	56	A
Pulsed Drain Current ¹⁾	I_{DM}	360	A
Power Dissipation ³⁾ ($T_C=25^{\circ}\text{C}$)	P_D	113	W
Thermal Resistance, Junction-to-Case	$R_{\theta JC}$	1.1	$^{\circ}\text{C}/\text{W}$
Single pulse avalanche energy ²⁾	E_{AS}	400	mJ
Junction Temperature	T_J	150	$^{\circ}\text{C}$
Storage Temperature Range	T_{STG}	$-55 \sim +150$	$^{\circ}\text{C}$

Electrical characteristics ($T_J=25^{\circ}\text{C}$, unless otherwise noted)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
Drain-source breakdown voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D =250μA	80			V
Zero gate voltage drain current	I _{DSS}	V _{DS} =80V, V _{GS} = 0V			1	μA
Gate-body leakage current	I _{GSS}	V _{GS} =±20V, V _{DS} = 0V			±100	nA
Gate threshold voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =250μA	2	3	4	V
Drain-source on-resistance	R _{DS(on)}	V _{GS} =10V, I _D =45A		2.6	3.3	mΩ
		V _{GS} =10V, I _D =20A		2.6	3.3	
Dynamic characteristics ⁴⁾						
Input Capacitance	C _{iss}	V _{DS} =40V, V _{GS} =0V, f =1MHz		4450		pF
Output Capacitance	C _{oss}			750		
Reverse Transfer Capacitance	C _{rss}			30		
Total Gate Charge	Q _g	V _{DS} =40V, V _{GS} =10V, I _D =45A		84		nC
Gate-Source Charge	Q _{gs}			12		
Gate-Drain Charge	Q _{gd}			11		
Turn-on delay time	t _{d(on)}	V _{DD} =40V, V _{GS} =10V, I _D =45A, R _{GEN} =3Ω		24		nS
Turn-on rise time	t _r			7		
Turn-off delay time	t _{d(off)}			57		
Turn-off fall time	t _f			23		
Source-Drain Diode characteristics						
Diode Forward Current	I _S				90	A
Diode Forward voltage	V _{SD}	V _{GS} =0V, I _S =45A			1.2	V
Reverse Recovery Time	t _{rr}	I _F =45A, di/dt =100A/μs		62		nS
Reverse Recovery Charge	Q _{rr}			82		nC

Notes:

- 1) Repetitive rating; pulse width limited by max. junction temperature.
- 2) $T_J=25^{\circ}\text{C}$, $V_{DD}=50V, V_G=10V, R_G=25\Omega, L=2mH, I_{AS}=20A$.
- 3) P_d is based on max. junction temperature, using junction-case thermal resistance.
- 4) Guaranteed by design, not subject to production testing.

Typical Characteristics




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Capacitance Characteristics




Figure 4. Gate Charge




Figure 5. On-Resistance vs Gate to Source Voltage




Figure 6. Normalized On-Resistance

Typical Characteristics




Figure 7. $R_{DS(on)}$ VS Drain Current




Figure 8. Forward characteristics of reverse diode




Figure 9. Normalized breakdown voltage




Figure 10. Normalized Threshold voltage




Figure 11. Current dissipation




Figure 12. Power dissipation

Typical Characteristics




Figure 13. Maximum Transient Thermal Impedance





Figure 14. Safe Operation Area

PDFN5*6-8L Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
D	5.150	5.550	0.203	0.219
E	5.950	6.150	0.234	0.242
A	0.850	1.000	0.033	0.039
A1	0.203 BSC.		0.008 BSC.	
A2	0.000	0.080	0.000	0.003
D1	4.250	4.450	0.167	0.175
E1	3.525	3.725	0.139	0.147
D2	5.200 REF.		0.205 REF.	
E2	5.550 REF.		0.219 REF.	
L1	0.450	0.650	0.018	0.026
L2	0.680 BSC.		0.027 BSC.	
b	0.300	0.500	0.012	0.020
e	1.270 BSC.		0.050 BSC.	