

Features

- Small body outline dimensions
- Low body height
- Stand off voltage: 3.3V, 5.0V, 7.0V, 12V, 24V
- Low leakage
- Response time is typically < 1 ns
- Provide transient protection:
IEC 61000-4-2 (ESD) level 4
IEC 61000-4-4 (EFT) 40A (5/50ns)
IEC 61000-4-5 (Surge) (8/20us)
- Lead-free parts meet RoHS requirements.
- Compliant to Halogen-free.


Applications

- Cellular phones
- Portable devices
- Digital cameras
- Power supplies

Mechanical data

- Epoxy:UL94-V0 rated flame retardant
- Case : Molded plastic, SOD-523
- Terminals : Solder plated, solderable per MIL-STD-750, Method 2026
- Polarity : Indicated by cathode band
- Mounting Position : Any

Package outline



Dimensions in inches and (millimeters)

Maximum ratings (at $T_A=25^\circ\text{C}$ unless otherwise noted)

PARAMETER	CONDITIONS		Symbol	Value	UNIT
Total power dissipation	Peak pulse power ($t_p = 8/20\mu\text{s}$)		P_{PP}	200	W
Electrostatic discharge	IEC61000-4-2 air discharge IEC61000-4-2 contact discharge		E_{SD}	± 20 ± 20	kV
ESD voltage	Per human body model		E_{SD}	16	kV
Electrostatic discharge	IEC61000-4-4		E_{FT}	40	A
Lead solder temperature-maximum	10 second duration		T_L	260	°C
Maximum junction temperature			T_J	+125	°C
Storage temperature range			T_{STG}	-55~+150	°C
Operating temperature range			T_{OP}	-40~+125	°C


Electrical characteristics (at $T_A=25^\circ\text{C}$ unless otherwise noted, $V_F = 0.9\text{V Max.}$ @ $I_F=10\text{mA}$ for all types)

Part No.	V_{RWM} (V) Max.	$I_R(uA)$ @ V_{RWM} Max.	$V_{BR}(V)$ @ I_T (Note 2) Min.	I_T (mA) Max.	$V_c(V)$ (Note 1) @ $I_{PP}=5.0\text{A}$ Max.	$I_{PP}(\text{A})$ (Note 1) Max.	$V_c(V)$ (Note 1) @Max I_{PP} Max.	P_{PK} (W) (Note 1) Max.	$C_J(\text{pF})$ $V_R=0\text{V}$ and $f=1\text{MHz}$ Typ.
ESD5Z3.3	3.3	1.0	5.0	1.0	8.4	11.2	14.1	158	105
ESD5Z5.0	5.0	1.0	6.2	1.0	11.6	9.4	18.6	174	80
ESD5Z7.0	7.0	1.0	7.5	1.0	13.5	8.8	22.7	200	65
ESD5Z12	12.0	1.0	13.5	1.0	17.0	9.6	25.0	240	55
ESD5Z24	24.0	10.0	26.7	1.0	Typ.48@ $I_{PP}=1\text{A}$	4.0	60.0	240	40

Note 1. Surge current waveform per Fig.1

2. V_{BR} is measured with a pulse test current I_T at an ambient temperature of 25°C .

Typical characteristics (at $T_A=25^\circ\text{C}$ unless otherwise noted)



V_C : Clamping Voltage @ I_{PP}

I_{PP} : Maximum Reverse Peak Pulse Current

V_{RWM} : Maximum Working Peak Reverse voltage

I_R : Maximum Reverse Leakage Current @ V_{RWM}

V_{BR} : Breakdown voltage @ I_T

I_T : Test Current

I_F : Forward Current

V_F : Forward Voltage @ I_F

C_J : Capacitance @ $V_R = 0\text{V}$ and $f = 1\text{MHz}$

Rating and characteristic curves (ESD5Z SERIES)

FIG.1: Pulse waveform (8/20μs)






FIG.2: Pulse derating curve




Application Note

Electrostatic discharge (ESD) is a major cause of failure in electronic system. Transient Voltage Suppressors (TVS) are an ideal choice for ESD protection. They are capable of clamping the incoming transient to a low enough level such that damage to the protected semiconductor is prevented. Surface mount TVS offers the best choice for minimal lead inductance. They serve as parallel protection elements, connected between the signal lines to ground. As the transient rise above the operating voltage of the device, the TVS becomes a low impedance path diverting the transient current to ground. The ESD5Z Series is the ideal board level protection of ESD sensitive semiconductor components. The tiny SOD-523 package allows design flexibility in the design of high density boards where the space is at a premium. This enables to shorten the routing and contributes to hardening against ESD.




Pinning information

Pin	Simplified outline	Symbol
Pin1 cathode Pin2 anode	1  2	1  2

Marking

Type number	Marking code
ESD5Z3.3	ZE
ESD5Z5.0	ZF
ESD5Z7.0	ZH
ESD5Z12	ZM
ESD5Z24	24

Suggested solder pad layout



Dimensions in inches and (millimeters)

PACKAGE	A	B	C
SOD-523	0.032 (0.80)	0.024 (0.60)	0.044 (1.10)