


Features

- Ultra Low Forward Voltage Drop .
- Very low profile-typical height of 1.10mm
- Low Power Losses,High Efficiency Operation
- Low Thermal Resistance Package.
- High Operating Junction Temperature.
- Compliant to Halogen-free
- Suffix "-Q1" for AEC-Q101

Mechanical data

- Epoxy:UL94-V0 rated flame retardant
- Case : TO-277B , molded Plastic
- Terminals:Solderable per MIL-STD-750,Method 2026
- Marking:SL1060

Package outline



Maximum ratings (AT $T_A=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	SL1060-T-Q1	Unit
DC Blocking Voltage	V_{DC}	60	V
Working Peak Reverse Voltage	V_{RWM}	60	V
Repetitive Peak Reverse Voltage	V_{RRM}	60	V
RMS Reverse Voltage	V_{RMS}	42	V
Average Forward Rectified Current	$I_{F(AV)}$	10.0	A
Peak Forward Surge Current,8.3ms Half Sine-wave($T_A=25^{\circ}\text{C}$)	I_{FSM}	250	A
Operating junction temperature range	T_J	-55 to +150	$^{\circ}\text{C}$
Storage temperature range	T_{STG}	-55 to +150	$^{\circ}\text{C}$

Electrical Characteristics (AT $T_A=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Test Conditions	Symbol	MIN.	TYP.	MAX.	Unit
Reverse Breakdown Voltage	$I_R=0.5\text{mA}, T_J=25^{\circ}\text{C}$	V_B	60	-	-	V
Forward voltage	$I_F=8\text{A}, T_J=25^{\circ}\text{C}$	V_F	-	0.42	-	V
	$I_F=10\text{A}, T_J=25^{\circ}\text{C}$		-	0.45	0.55	
Reverse current	$V_R=60\text{V}, T_J=25^{\circ}\text{C}$	I_R	-	0.051	0.3	mA
	$V_R=60\text{V}, T_J=100^{\circ}\text{C}$		-	5	15	
	$V_R=60\text{V}, T_J=150^{\circ}\text{C}$		-	27	75	






Thermal Characteristics

Parameter	Symbol	SL1060-T-Q1	Unit
Typical thermal resistance junction to ambient ,Note 1	$R_{\theta JA}$	73	$^{\circ}\text{C}/\text{W}$
Typical thermal resistance junction to ambient ,Note 2	$R_{\theta JA}$	31	$^{\circ}\text{C}/\text{W}$



Note : 1.FR-4 PCB, 2oz.Copper.

2.Polyimide PCB, 2oz.Copper.Cathode pad dimensions 18.8mm x 14.4mm.Anode pad dimensions 5.6mm x 14.4mm.


Rating and characteristic curves



Pinning information


Pin	Simplified outline	Symbol
Pin2 cathode Pin1 anode Pin3 anode		

Marking

Type number	Marking code
SL1060-T-Q1	

Suggested solder pad layout

TO-277B



Dimensions in inches and (millimeters)